



Zaślepki gwintowane

(wymiary i gwinty podane w calach)

Część 64



Łączenie na wcisk



Wymiary rury											Maks. obciążenie	
ø Zewnętrzna		Grubość		ø Wewnętrzna	Gwint D		D1	D2	H	L	Kod	statyczne
(cale)	(mm)	(cale)	(mm)	(mm)	(UNC)	(mm)	(mm)	(mm)	(mm)	(mm)		(N)
1"	(25,4)	0,083"	(2,1)	21,18	1/4"-20	(6,35)	25,2	21,18	6	26	64 / 82730	4500
					5/16"-18	(7,93)	25,2	21,18	6	26	64 / 82731	4500
1" 1/4	(31,75)	0,083"	(2,1)	27,53	3/8"-16	(9,52)	31,5	27,53	6	31	64 / 82732	5000
					1/2"-13	(12,7)	31,5	27,53	6	31	64 / 82733	5000
					5/8"-11	(15,87)	31,5	27,53	6	31	64 / 82734	6500
					3/8"-16	(9,52)	38	34,8	8	38	64 / 82695	5000
1" 1/2	(38,1)	0,065"	(1,65)	34,8	1/2"-13	(12,7)	38	34,8	8	38	64 / 82696	5000
					5/8"-11	(15,87)	38	34,8	8	38	64 / 82697	6500
					3/4"-10	(19,05)	38	34,8	8	38	64 / 82698	9000
					3/8"-16	(9,52)	38	33,89	8	38	64 / 82735	5000
		0,083"	(2,1)	33,89	1/2"-13	(12,7)	38	33,89	8	38	64 / 82736	5000
					5/8"-11	(15,87)	38	33,89	8	38	64 / 82737	6500
					3/4"-10	(19,05)	38	33,89	8	38	64 / 82738	9000
					5/8"-11	(15,87)	44,2	38,35	8	38	64 / 82740	6500
1" 3/4	(44,45)	0,12"	(3,04)	38,35	3/4"-10	(19,05)	44,2	38,35	8	38	64 / 82741	9000
					1"-8	(25,4)	44,2	38,35	8	38	64 / 82739	10000
					3/8"-16	(9,52)	50,6	47,5	10	45	64 / 82703	5000
2"	(50,8)	0,065"	(1,65)	47,5	1/2"-13	(12,7)	50,6	47,5	10	45	64 / 82704	5000
					5/8"-11	(15,87)	50,6	47,5	10	45	64 / 82705	6500
					3/4"-10	(19,05)	50,6	47,5	10	45	64 / 82706	9000
					3/8"-16	(9,52)	50,6	45,26	10	45	64 / 82699	5000
		0,109"	(2,77)	45,26	1/2"-13	(12,7)	50,6	45,26	10	45	64 / 82700	5000
					5/8"-11	(15,87)	50,6	45,26	10	45	64 / 82701	6500
					3/4"-10	(19,05)	50,6	45,26	10	45	64 / 82702	9000
					5/8"-11	(15,87)	50,6	42,88	10	45	64 / 82742	6500
		0,156"	(3,96)	42,88	3/4"-10	(19,05)	50,6	42,88	10	45	64 / 82743	9000
					1"-8	(25,4)	50,6	42,88	10	45	64 / 82744	10000
					5/8"-11	(15,87)	63,3	55,58	12	52	64 / 82745	6500
2" 1/2	(63,5)	0,156"	(3,96)	55,58	3/4"-10	(19,05)	63,3	55,58	12	53	64 / 82746	9000
					1"-8	(25,4)	63,3	55,58	12	52	64 / 82747	10000

Materiały: Zaślepka ze wzmocnionego poliamidu, kolor czarny; gwintowana wkładka z mosiądzu.

Opakowanie: 24 sztuki.

Na żądanie

- Zaślepki: różnej grubości i w różnych kolorach.
- Wkładka gwintowana: z mosiądzu niklowanego.
- Opakowania: niestandardowe.